

nommi

GENERATOR
RANGE

BRING BLUE ENERGY ON BOARD WITH OUR GENERATOR RANGE FROM 5 KW TO 800 KW



Nanni's expertise extends beyond marine engine to generators in order to bring energy on board.

Our marine soundproofed generator sets are meticulously crafted to meet the diverse needs of boat owners. Available in models ranging from Q500 to Q6800, with power outputs from 5 to 150 kW, it provides the ideal power solution to create a serene journey on the seas. This range will be expanded during year 2023.

MODELS	KW	HZ	PHASE	EMISSIONS
Q500	5kw	50	Mono	IMO II & RC2
Q1100	7,6kw to 11 kW	50 & 60	Mono / Triphase	IMO II, EPA Tier III & RC2
Q1500	9,6kw to 15,4 kW	50 & 60	Mono / Triphase	IMO II, EPA Tier III & RC2
Q2400	18kw to 27,8 kW	50 & 60	Mono / Triphase	IMO II, EPA Tier III & RC2
Q3300	24,9kw to 36,4kW	50 & 60	Mono / Triphase	IMO II, EPA Tier III & RC2
Q3800	32kw to 47 kW	50	Mono / Triphase	IMO II, EPA Tier II & RC2
Q4500	45kw to 99 kW	50 & 60	Triphase	IMO II, EPA Tier III & RC2
Q6800	99kw to 150 kW	50 & 60	Triphase	IMO II, EPA Tier III & RC2

CUSTOMER BENEFITS

- Compact Design & Easy Maintenance
- Powered by a four-stroke diesel engine
- Cooling by heat exchanger sea water and cooling liquids

CONTROL PANEL Si2

- On & off buttons
- Illustrated Menu



- Display and management of motor parameters
- Display and management of generator parameters
- Generator status indicator
- Display of alerts and fault codes
- GCB (Generator Circuit Breaker) button option
- History log (150 records)
- 5 languages available
- 172 x 112 mm

AVAILABLE OPTIONS

- Governor and parallel kit 12V
- Isolated ground: bipolar insulation for metal hulls (aluminum and steel)
- Syphon breaker kit
- Exhaust system kit


THE NEXT STEP TOWARDS ONBOARD SILENCE: SOUNDLESS VERSION

All our teams work tirelessly to deliver products that meet all our customers' needs as they explore the world's oceans. We know how important it is to have the right engineering on board to power all the equipment needed for the best and safest navigation. But isn't it better to enjoy the quiet reverie of our blue planet without any noise?

That is why we are pleased to present the brand-new SOUNDLESS version of our generators with sound shield. This technology with improved acoustic materials allows us to reduce the sound level to 61.7, the lowest on the market today.



Sound Enclosure with Wet Exhaust	Load	Distance	Sides	DbA
	No Load	1 m 3.3 ft	A	61.7
			B	61.2
			C	62.2
			D	61.8
	4 sides avg.*			61.7



*Measurement are registered according ISO standard, in anechoic chamber. Measurement may change +/- 1.5 DbA according to environnement conditions.

nanni



ENERGY IN BLUE

NANNI INDUSTRIES S.A.S.

11, avenue Abbé Mariotte
33260 La Teste de Buch
France
TEL +33 (0) 556 22 30 60

NANNI SRL

Via degli Olmetti, 44/A
00060 Formello – Roma
Italia
TEL +39 06 30 88 42 51

www.nannienergy.com

